



Type 30B Seal Design

DASH	A SHAFT	B SEAL OD	C BORE (MIN)	D OP LENGTH +.050/- .020	E SET SCREW	F DIST TO SHAFT STEP	G SHAFT STEP DIA	H FACE OD (MAX)	J FACE ID (MIN)
-8	0.500	0.938	1.063						
-10	0.625	1.063	1.188						
-16	1.000	1.438	1.563	1.313	1.127	0.969	0.875	1.201	0.931
-18	1.125	1.563	1.688	1.375	1.190	1.031	1.000	1.326	1.056
-20	1.250	1.688	1.813	1.375	1.190	1.031	1.125	1.451	1.181
-22	1.375	1.938	2.063	1.688	1.477	1.344	1.125	1.562	1.292
-24	1.500	1.938	2.063	1.438	1.252	1.094	1.250	1.715	1.405
-26	1.625	2.188	2.375	1.594	1.383	1.156	1.375	1.840	1.530
-28	1.750	2.313	2.438	1.750	1.548	1.156	1.500	1.975	1.665
-30	1.875	2.500	2.625	1.750	1.540	1.156	1.625	2.100	1.790
-32	2.000	2.625	2.750	1.750	1.540	1.156	1.750	2.227	1.917
-34	2.125	2.750	2.938	2.062	1.852	1.563	1.875	2.352	2.042
-36	2.250	2.844	2.969	1.750	1.540	1.250	2.000	2.507	2.137
-38	2.375	3.000	3.125	2.062	1.852	1.563	2.125	2.644	2.274
-40	2.500	3.125	3.250	1.750	1.540	1.250	2.250	2.769	2.399
-42	2.625	3.250	3.375	2.062	1.852	1.563	2.375	2.894	2.524
-44	2.750	3.375	3.500	2.062	1.852	1.563	2.500	3.019	2.649
-46	2.875	3.500	3.625	2.062	1.852	1.563	2.625	3.144	2.774
-48	3.000	3.625	3.750	2.062	1.852	1.563	2.750	3.269	2.899
-50	3.125	3.750	3.875	2.062	1.852	1.500	2.875	3.396	3.026
-52	3.250	3.875	4.000	2.062	1.852	1.500	3.000	3.521	3.151
-54	3.375	4.000	4.125	2.062	1.852	1.500	3.125	3.686	3.240
-56	3.500	4.125	4.250	2.062	1.852	1.500	3.250	3.811	3.365
-60	3.750	4.375	4.500	2.062	1.852	1.500	3.500	4.061	3.615