



Type 30 Seal Design

DASH	A SHAFT	B SEAL OD	C BORE (MIN)	D OP LENGTH +.050/- .020	E SET SCREW	F FACE OD (MAX)	G FACE ID (MIN)
-8	0.500	0.938	1.063	0.813	0.647	0.802	0.620
-10	0.625	1.063	1.188	0.750	0.585	0.927	0.745
-16	1.000	1.438	1.563	1.000	0.815	1.303	1.119
-18	1.125	1.563	1.688	1.000	0.815	1.430	1.242
-20	1.250	1.688	1.813	1.000	0.815	1.552	1.370
-22	1.375	1.938	2.063	1.125	0.915	1.715	1.495
-24	1.500	1.938	2.063	1.125	0.940	1.802	1.620
-26	1.625	2.188	2.375	1.156	0.946	1.953	1.745
-28	1.750	2.313	2.438	1.375	1.173	2.078	1.870
-30	1.875	2.500	2.625	1.375	1.165	2.215	1.995
-32	2.000	2.625	2.750	1.375	1.165	2.340	2.120
-34	2.125	2.750	2.938	1.688	1.477	2.465	2.245
-36	2.250	2.844	2.969	1.375	1.165	2.576	2.370
-38	2.375	3.000	3.125	1.688	1.477	2.715	2.495
-40	2.500	3.125	3.250	1.375	1.165	2.840	2.620
-42	2.625	3.250	3.375	1.688	1.477	2.965	2.745
-44	2.750	3.375	3.500	1.688	1.477	3.090	2.870
-46	2.875	3.500	3.625	1.688	1.477	3.215	2.995
-48	3.000	3.625	3.750	1.688	1.477	3.340	3.120
-50	3.125	3.750	3.875	1.688	1.477	3.465	3.245
-52	3.250	3.875	4.000	1.688	1.477	3.590	3.370
-54	3.375	4.000	4.125	1.688	1.477	3.715	3.495
-56	3.500	4.125	4.250	1.688	1.477	3.840	3.620
-60	3.750	4.375	4.500	1.688	1.477	4.090	3.870